SO 9001 SO 14001

# Tecfi S.p.A. - Fixing Systems

Head Office:

S.S. Appia km.193 - 81050 Pastorano (CE) - Italy tel. (+39).0823.88.33.38 - fax (+39).0823.88.32.60 www.tecfi.it info@tecfi.it

# **Declaration of Performance No TECFVLU19-001**

According to the Regulation EU No 305/2011

# **VLU**

Manufacturer: Tecfi S.p.A. - S.S. Appia, km 193 - 81050 Pastorano (CE), Italia



1 - Intended use				
Product type	Sealants			
Category	- Sealant for non structural use in joints in buildings - Sealant for façade elements for interior and exterior application			
Thecnical description of the product	see Table 4			
In accordance with the applicable harmonised technical specification	EN 15651-1: F-EXT-INT-CC; 20LM EN 15651-2:2012 : Tipo G-CC; 20LM			
Besic material	Acetic silicone			
Installation	see Table 2			
System or systems of assessment and verification of constancy of performance of the construction product, as set out in Annex V	System 3 System 3: for reaction fire			
Notified body	ZAG, NB 1404 has carried out Determination of Product Type under system 3			
Under the system	3			

#### 2 - Installation




Carefully clean the joint to be sealed



Use adhesive tape on the edges of the joint




Open the cartridge



Seal using the nozzle




Finish the sealing with a wet spatula



Remove the adhesive tape before the curing

### 3 - Item Code

3 - Item Code						
Item Code Color		Cartridge Capacity				
VLU 00 00 280	Transparent	280 ml				
VLU 01 00 280	White	280 ml				





Head Office: S.S. Appia km.193 - 81050 Pastorano (CE) - Italy tel. (+39).0823.88.33.38 - fax (+39).0823.88.32.60 www.tecfi.it info@tecfi.it



# **Declaration of Performance No TECFVLU19-001**

According to the Regulation EU No 305/2011

# **VLU**

Manufacturer: Tecfi S.p.A. - S.S. Appia, km 193 - 81050 Pastorano (CE), Italia



4 - Declarede Performances						
Essential characteristics	Performance	Harmonised technical specification				
TYPE F: EXT-INT	'					
Reaction to fire	Class E					
Resistance to flow	≤ 3 mm					
Loss of Volume	≤ 45 %					
Adhesion / cohesion maintained extension after water immersion	NF	EN 15051 1				
Elastic recovery	≥ 40 %	EN 15651-1				
Tensile properties at maintained extension	NF					
Adhesion / cohesion at variable temperatures	NF					
Durability	Pass					



ISO 9001 ISO 14001

#### Tecfi S.p.A. - Fixing Systems

Head Office:

S.S. Appia km.193 - 81050 Pastorano (CE) - Italy tel. (+39).0823.88.33.38 - fax (+39).0823.88.32.60 www.tecfi.it info@tecfi.it

### **Declaration of Performance No TECFVLU19-001**

According to the Regulation EU No 305/2011

#### **VLU**

Manufacturer: Tecfi S.p.A. - S.S. Appia, km 193 - 81050 Pastorano (CE), Italia



#### 5 - Label



The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

8.6.4.		_		
Name and function	Place and date of issue		Sig	gnature
President	Pastorano, June 3 <sup>th</sup> 2019		/	1 1
Antonio Guarino			M	γu (l)