

## **Declaration of Performance VR 14001**

according to Regulation EU 305/2011

Item code: VR03, VR04, VR05, VR24

Manufacturer: Tecfi S.p.A. - S.S. Appia, km 193 - 81050 Pastorano (CE), Italy

1. Intended use	
Product type:	Sealants
Category:	Sealant for non-structural use in joints in buildings and pedestrian walkways
Technical description of the	- sealants for façade elements
product:	- sealants for glazing
Intended as laid down in the related harmonized standard:	EN 15651-1: F-EXT-INT-CC / Sealant for non-structural use in joints in buildings and pedestrian walkways: sealants for façade elements EN 15651-2: G-CC / Sealant for non-structural use in joints in buildings and pedestrian walkways: sealants for glazing
Class of sealants	25 LM
Notified body:	SKZ TeConA GmbH n° 01213
AVCP:	3
Conditioning:	Method A (ISO 8340)
Substrate:	Glass (without primer), Aluminum (without primer), Mortar M1 (with primer G783)

2. Essential characteristics according to EN 15651-1				
Application:	F-EXT-INT-CC class 25 LM			
Reaction to fire (EN13501)	class E			
Release of dangerous substances:	See MSDS			
Resistance to flow (ISO 7390):	≤ 2 [mm]			
Loss of volume (ISO 10563):	≤ 10%			
Tensile properties – elongation at break – after water immersion (ISO 10590):	pass			
Elastic recovery (ISO 8339):	≥70% (F); ≥60% (G);			
Durability:	pass			

Sede operativa, stabilimento e corrispondenza: S.S. Appia km.193 - 81050 Pastorano (CE) - Italia tel. (+39).0823.88.33.38 - fax (+39).0823.88.32.60 www.tecfi.it info@tecfi.it

## **Declaration of Performance VR 14001**

according to Regulation EU 305/2011

3. Essential characte	eristics according to EN 15651-2
Application:	G-CC class 25 LM
Reaction to fire (EN13501)	class E
Release of dangerous substances:	See MSDS
Resistance to flow (ISO 7390):	≤ 3 [mm]
Loss of volume (ISO 10563):	1 < 10%
Elastic recovery (ISO 7389)	≥ 60%
Durability:	pass

4. Item codes		
Cartridge capacity	Cartridge type	Item codes
300 ml	Rigid	VR 03 00 300
300 ml	Rigid	VR 04 00 300
300 ml	Rigid	VR 05 00 300
300 ml	Rigid	VR 24 00 300

The performances of the product identified by the above identification code are in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of Tecfi S.p.A.

Signed for and behalf of the manufacturer by:

_	ighted for and behalf of the managactarer s	· y ·					
	Name and function	Place and date of issue		Sign	Signature		
	<i>President</i> Antonio Guarino	Pastorano, September 14 <sup>th</sup> 2015	X	My	un P		
			/	(			