

Declaration of Performance No ZR14001

According to the Regulation EU No 305/2011

ZR


Manufacturer: Tecfi S.p.A. - S.S. Appia, km 193 - 81050 Pastorano (CE), Italia




1 - Uso previsto

Product-type:	Sealant
Category:	Sealant for non-structural use in joints in buildings and pedestrian walkways
Technical description of the product:	- Sealants for façade elements - Sealants for pedestrian walkways
Intended use as laid down in the related harmonized standard:	EN 15651-1: F-EXT-INT-CC / Sealant for non-structural use in joints in buildings and pedestrian walkways: Sealants for façade elements EN 15651-4: PW-EXT-INT-CC / Sealant for non-structural use in joints in buildings and pedestrian walkways: Sealants for pedestrian walkways
Class of sealant:	25 LM
Notified body:	4 Ward Testing n° 2538
AVCP:	3
Substrate:	Mortar M1 (with primer)


2 - Installation




Carefully clean the joint to be sealed




Use adhesive tape on the edges of the joint




Open the cartridge



Seal using the nozzle



Finish the sealing with a wet spatula



Remove the adhesive tape before the curing

3 - Item Code

Item Code	Color	Cartridge Capacity
VR 03 00 300	Grigio	300 ml

Declaration of Performance No ZR14001

According to the Regulation EU No 305/2011

ZR

Manufacturer: Tecfi S.p.A. - S.S. Appia, km 193 - 81050 Pastorano (CE), Italia



4 - Essential characteristics according to EN 15651-1 and EN 15651-4

Essential characteristics	Performance	Harmonised technical specification
Applications:	F-EXT-INT-CC PW EXT-INT-CC	EN 15651-1:2012 EN 15651-4:2012
Fire reaction (EN 13501):	class E	
Release of chemicals dangerous to the environment and health	See material safety data sheet:	
Water tightness and air tightness:		
Resistance to flow (ISO 7390):	≤ 3 [mm]	
Loss of volume (ISO 10563):	≤ 10%	
Tensile properties - maintained extension after water immersion (ISO 15590)	pass	
Tensile properties - maintained extension (ISO 8340)	pass	
Tensile properties - maintained extension at - 30°C (ISO 8340)	pass	
Tensile properties - Secant modulus at 23°C (ISO 8339)	≤ 0.4 MPa	
Tensile properties - Secant modulus at - 20°C (ISO 8339)	≤ 0,6 MPa	
Tensile properties - Secant modulus at - 30°C (ISO 8339)	≤ 0,9 MPa	
Tensile properties - maintained extension after water immersion 28 days (ISO 10590):	pass	
Tensile properties - maintained extension after salted water immersion 28 days (ISO 10590)	pass	
Tear resistance	pass	
Durability:	pass	



Declaration of Performance No ZR14001

According to the Regulation EU No 305/2011

ZR

Manufacturer: Tecfi S.p.A. - S.S. Appia, km 193 - 81050 Pastorano (CE), Italia

5 - Etichetta

The image shows a detailed product label for Tecfi Sigillante Poliuretano Medio Alto Modulo Professional. The label is divided into several sections:

- 1**: QR Code at the bottom right.
- 2**: Product name and description: 'Sigillante Poliuretano MEDIO ALTO MODULO PROFESSIONALE'.
- 3**: Applications: 'Ideoneo per sigillature e incollaggi di: Giunti a pavimento e di dilatazione in edilizia, Metalli, Legno, Calcestruzzo, Materiali edili in genere.' and 'Suitable for sealings and bonding of: Floor joints, Metals, Wood, Concrete, Building materials.'
- 4**: Images showing the product being used on various surfaces like floors and walls.
- 5**: Certifications: CE mark, Tecfi S.p.A. 17, and ISO 11600-F-25HM.
- 6**: Content: '300 ml e'.
- 7**: Symbols: Hazardous, Dangerous, and Made in E.U.
- 8**: Safety symbols: Health hazard, Environment, and Flame.
- 9**: 'MODALITÀ DI IMPIEGO' (How to use) section.
- 10**: 'CAMPI DI IMPIEGO' (Where to use) section.

- | | |
|---|---|
| 1 Codice articolo / Item Code | 6 QR Code |
| 2 Descrizioni / Descriptions | 7 Contenuto (ml) / Contents (ml) |
| 3 Utilizzi / Usages | 8 Simboli / Symbols |
| 4 Esempi di utilizzo / Examples of use | 9 Modalità di impiego / How to use |
| 5 Certificazioni / Certifications | 10 Campi di impiego / Where to use |

The performances of the product identified by the above identification code are in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of Tecfi S.p.A.

Signed for and behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
President Antonio Guarino	Pastorano, September 18 th 2017	