






NK - NM - NP - NQ Vite a legno Testa a Goccia di Segò impronta a 6 lobi, in acciaio INOX A2, assemblata con rondella 


 **SCHEDA TECNICA**




D x L	diametro vite x lunghezza vite
d	misura rondella




NK
Vite: Acciaio Inox A2
Rondella: Acciaio Inox A2/EPDM



NM
Vite: Acciaio Inox A2 ramata
Rondella: Rame/EPDM



NP
Vite: Acciaio Inox A2 verniciata
RAL 9002 bianco grigiastro
Rondella: Acciaio Inox A2/EPDM



NQ
Vite: Acciaio Inox A2 verniciata
RAL 8017 marrone cioccolato
Rondella: Acciaio Inox A2/EPDM

DATI TECNICI E RISULTATI DI PROVA SU VITI NK - NM - NP - NQ

Codice Articolo	Misura Vite D x L (mm)	d (mm)	CARICO CARATTERISTICO (kN) ESTRAZIONE
Rondella Ø 15			
NK 15 45 025 - NM 15 45 025	4,5 x 25	15	2,10
NK 15 45 035 - NM 15 45 035	4,5 x 35		
NK 15 45 045 - NM 15 45 035	4,5 x 45		
Rondella Ø 20			
NK 20 45 025 - NM 20 45 025 - NP 20 45 025 - NQ 20 45 025	4,5 x 25	20	2,91
NK 20 45 035 - NM 20 45 035 - NP 20 45 035 - NQ 20 45 035	4,5 x 35		
NK 20 45 045 - NM 20 45 045 - NP 20 45 045 - NQ 20 45 045	4,5 x 45		
NK 20 45 060 - NM 20 45 060 - NP 20 45 060 - NQ 20 45 060	4,5 x 60		
NK 20 45 080 - NM 20 45 080	4,5 x 80		
NK 20 45 100 - NM 20 45 100	4,5 x 100		


 Per i dati non inseriti in tabella rivolgersi al Laboratorio Tecfi

NK - NM - NP - NQ

A2 stainless steel 6-lobe raised countersunk head wood screw assembled with washer





TECHNICAL DATA SHEET



D x L screw diameter x screw length


d washer diameter



NK

Screw: A2 Stainless steel


Washer: A2 Stainless steel /EPDM



NM

Screw: A2 Stainless steel copper

Washer: copper




NP

Screw: RAL 9002 grey white

Painted A2 stainless steel

Washer: A2 Stainless steel /EPDM



NQ

Screw: RAL 8017 chocolate brown

Painted A2 stainless steel

Washer: A2 Stainless steel /EPDM

TECHNICAL DATA AND TEST REPORT OF Tecfi **NK - NM - NP - NQ** SCREWS

Item Code	Screw Size D x L (mm)	d (mm)	CHARACTERISTIC LOADS
			(kN) PULL OUT
Washer Ø 15			
NK 15 45 025 - NM 15 45 025	4,5 x 25	15	2,10
NK 15 45 035 - NM 15 45 035	4,5 x 35		
NK 15 45 045 - NM 15 45 035	4,5 x 45		
Washer Ø 20			
NK 20 45 025 - NM 20 45 025 - NP 20 45 025 - NQ 20 45 025	4,5 x 25	20	2,91
NK 20 45 035 - NM 20 45 035 - NP 20 45 035 - NQ 20 45 035	4,5 x 35		
NK 20 45 045 - NM 20 45 045 - NP 20 45 045 - NQ 20 45 045	4,5 x 45		
NK 20 45 060 - NM 20 45 060 - NP 20 45 060 - NQ 20 45 060	4,5 x 60		
NK 20 45 080 - NM 20 45 080	4,5 x 80		
NK 20 45 100 - NM 20 45 100	4,5 x 100		

For all specification not included in the table, please contact Tecfi Lab